

## QUATRO "LIGHTWEIGHT" L1200HP WORM DRIVE W/CAT C32

Stroke per min.			180	120	80	40
L 1200 hp	Hydraulic hp		1080	720	480	240
Liner size in. (mm)	Gal/stk (Liters/stk)	Max discharge pressure PSI (kg/cm <sup>2</sup> )	GPM - Gallons per minute (LPM - Liters per minute)			
7 (177.8)	5.33 (20.18)	1929 (142)	960 (3632)	640 (2421)	426 (1614)	213 (807)
6.5 (165.1)	4.60 (17.40)	2238 (164)	827 (3132)	552 (2088)	368 (1392)	184 (696)
6 (152.4)	3.92 (14.83)	2626 (193)	705 (2669)	470 (1779)	313 (1186)	157 (593)
5.5 (139.7)	3.29 (12.46)	3125 (230)	592 (2242)	395 (1495)	263 (997)	132 (498)
5 (127)	2.72 (10.30)	3782 (278)	490 (1853)	326 (1235)	218 (824)	109 (412)
4.5 (114.3)	2.20 (8.34)	4669 (343)	397 (1501)	264 (1001)	176 (667)	88 (334)
4 (101.6)	1.74 (6.59)	5000 (367)	313 (1186)	209 (791)	139 (527)	70 (264)

Rated strokes and horsepower 180 SPM @ 1200 Input horsepower. Liners available in 1/2" sizes.  
 Hydraulic horsepower & flow rate based upon 90% mechanical efficiency and 100% volumetric efficiency.  
 All data subject to change without notification

Max input hp	1200
Pump speed	180 SPM
Stroke length	8" (203.2 mm)
Max. piston size	7" (177.8 mm)
Min. piston size	4" (101.6 mm)
Fluid end working pressure	500 PSI (51.71 Mpa)

Max. flow rate	960 GPM (3632 LPM)
Width	64" (1,625 mm)
Length	337" (8,559 mm)
Height	84.5" (2,146 mm)
Fluid module removal	25 min

